



173900	STANDARD - 3000K	MAX 700 mA DC - 10 W LED - 639 lm - CRI > 90
173900-27	STANDARD - 2700K	CAVO NERO 5 m - KIT INSTALLAZIONE OPZIONALE NON INCLUSO
		DIMENSIONI TAGLIO Ø 250 mm
		SPAZIO MINIMO PER INCASSO 350 mm
		ORIENTABILE
		DRIVER LED INCLUSO INPUT 220-240 V - 50/60 Hz - IP67 - NON DIMMERABILE
		BLACK CABLE 5 m - OPTIONAL INSTALLATION KIT NOT INCLUDED
		CUT-OUT Ø 250 mm
		MINIMUM SPACE FOR MOUNTING 350 mm
		ADJUSTABLE
		INCLUDES LED DRIVER INPUT 220-240 V - 50/60 Hz - IP67 - NOT DIMMABLE

KIT INSTALLAZIONE OPZIONALI / OPTIONAL INSTALLATION KITS

177300	STANDARD	TIRAFONDO INSTALLAZIONE / INSTALLATION ANCHORING DEVICE
--------	----------	---

ACCESSORI OPZIONALI / OPTIONAL ACCESSORIES

185104	NERO OPACO / MATT BLACK - 3000K	TESTA LED SUPPLEMENTARE / ADDITIONAL LED HEAD
185104-27	NERO OPACO / MATT BLACK - 2700K	700 mA DC - 10 W LED - 639 lm - CRI > 90

