

CETO

WALL LIGHT

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Wall Light reflects the shadows of the glass against the wall, replicating the natural flow and movement of water.

AVAILABLE FINISHES



FROSTED BLACK











TECHNICAL

MATERIAL

ANODISED ALUMINIUM, GLASS

LOW VOLTAGE LED

SELV 60V -

2-4W LED MODULE, WATTAGE VARIES DEPENDING ON CETO CONFIGURATION. 300-380 LUMEN RANGE PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. FXTFRNAL DRIVER SUPPLIED.

DIMMING -

PHASE - DIMMING RANGE 5 - 100%.
DALI - DIMMING RANGE 1 - 100%.
1-10V - DIMMING RANGE 5 - 100%.
0-10V - NOT COMPATIBLE.

IF THE CEILING CAVITY CANNOT HOUSE THE DRIVER PLEASE CONTACT THE STUDIO FOR FURTHER OPTIONS.

120V LED

4W AC LED MODULE - 380 LUMEN PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. DRIVER NOT

REQUIRED, DIRECT MAINS VOLTAGE.

DIMMING -

PHASE - DIMMING RANGE 5 - 100%.

DALI - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY

VIA DALI SWITCH. 1-10V - NOT COMPATIBLE. 0-10V - NOT COMPATIBLE.

ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE

REGIONS.

CONT. FOR OPTIMAL DIMMING PERFORMANCE WE

RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING

THE DIMMING RANGE OF THE FIXTURE.

PLEASE CONTACT OUR STUDIO FOR FURTHER INFORMATION REGARDING MOST SUITABLE LAMPING TECHNOLOGY FOR YOUR SPECIFIC PROJECT.

LED LIFESPAN 50.000 HRS

CANOPY BLACK (WITH BLACK ANODISED BODY) OR CHAMPAGNE

(WITH CHAMPAGNE ANODISED BODY)

IP RATING IP20 - FOR INDOOR USE ONLY

CERTIFICATION AS/NZS - 60598.2.1 EN - 60598.2.1

UL 1598, CSA C22.2#250.0

PRODUCT CODES SKU

EG. CW1.G-BLK.A-BLK = CETO WALL LIGHT IN BLACK GLASS WITH A BLACK

ANODISED CANOPY

CW1-G-XXX.A-XXX CETO STANDARD WALL LIGHT

FINISHES FOR ALL

VARIATIONS: GLASS: FROSTED BLACK (G-FBK)

BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT)

BODY: BLACK ANODISED (A-BLK)
CHAMPAGNE ANODISED (A-CHM)

DIMENSIONS VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*

WEIGHT 1.5KG / 3.5LB

PACKAGING L 25CM W 25CM H 15CM / L 9.8" W 9.8" H 5.9"

PACKAGING WEIGHT 2KG / 4.5LB

DIMENSIONS



CW1 Ø 200 D 87 Ø 7.9" D 3.4"

archiluce



CETO

WALL LIGHT - OFFSET

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Wall Light reflects the shadows of the glass against the wall, replicating the natural flow and movement of water.

AVAILABLE FINISHES



FROSTED BLACK





CLEAR



WHITE





TECHNICAL

MATERIAL ANODISED ALUMINIUM, GLASS

LOW VOLTAGE LED

SELV 60V -

2-4W LED MODULE, WATTAGE VARIES DEPENDING ON CETO CONFIGURATION. 300-380 LUMEN RANGE PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE.

EXTERNAL DRIVER SUPPLIED.

DIMMING -

PHASE - DIMMING RANGE 5 - 100%.
DALI - DIMMING RANGE 1 - 100%.
1-10V - DIMMING RANGE 5 - 100%.
0-10V - NOT COMPATIBLE.

IF THE CEILING CAVITY CANNOT HOUSE THE DRIVER PLEASE CONTACT THE STUDIO FOR FURTHER OPTIONS.

120V LED

4W AC LED MODULE - 380 LUMEN PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. DRIVER NOT

REQUIRED, DIRECT MAINS VOLTAGE.

DIMMING -

PHASE - DIMMING RANGE 5 - 100%.

DALI - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY

VIA DALI SWITCH. 1-10V - NOT COMPATIBLE. 0-10V - NOT COMPATIBLE.

ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE

REGIONS.

DIMENSIONS



CWL1 W 200 H 400 D 107 W 7.9" H 15.8" D 4.2"



CWL2 W 200 H 650 D 107 W 7.9" H 25.6" D 4.2" CONT. FOR OPTIMAL DIMMING PERFORMANCE WE

RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING

THE DIMMING RANGE OF THE FIXTURE.

PLEASE CONTACT OUR STUDIO FOR FURTHER INFORMATION REGARDING MOST SUITABLE LAMPING TECHNOLOGY FOR YOUR SPECIFIC PROJECT.

LED LIFESPAN 50,000 HRS

CANOPY BLACK (WITH BLACK ANODISED BODY) OR CHAMPAGNE

(WITH CHAMPAGNE ANODISED BODY)

IP RATING IP20 - FOR INDOOR USE ONLY

CERTIFICATION AS/NZS - 60598.2.1 EN - 60598.2.1

UL 1598, CSA C22.2#250.0

PRODUCT CODES SKU

EG. CWL1.G-BLK.A-BLK = CETO WALL LIGHT WITH OFFSET MOUNT IN BLACK

GLASS WITH A BLACK ANODISED BODY

CWL1-G-XXX.A-XXX CETO WALL LIGHT WITH OFFSET MOUNT CWL2-G-XXX.A-XXX CETO DOUBLE WALL LIGHT WITH OFFSET MOUNT

FINISHES FOR ALL

VARIATIONS: GLASS: FROSTED BLACK (G-FBK)

BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT)

BODY: BLACK ANODISED (A-BLK)
CHAMPAGNE ANODISED (A-CHM)

DIMENSIONS VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*

WEIGHT CWL1 - 2.5KG / 5.5LB

CWL2 - 4KG/9LB

PACKAGING CWL1 - L 51CM W 51CM H 25CM / L 20" W 20" H 9.8"

CWL2 - L 51CM W 51CM H 25CM / L 20" W 20" H 9.8"

PACKAGING WEIGHT CWL1 - 3.5KG / 7.5LB

CWL2 - 5KG / 11LB